

Evacuatable Pellet Dies

Make solid pellets from powder materials

Pellet dies are used to compress powders into solid form using a hydraulic press. Our pellets are made from the highest quality materials and manufactured to high dimensional tolerances to ensure the best results.

These pellet dies are particularly suited to making KBr pellets for FTIR spectroscopy and other spectroscopic techniques. However, almost any powder material can be compressed using these dies, including materials for solid-state chemistry, pharmaceuticals, and soil samples.

Key Features

- **Hardened stainless steel construction**
Increases durability and avoids excessive expansion under load.
- **Polished inner pressing faces**
Ensures smooth finish on pellets – important for spectroscopy applications.
- **Vacuum port**
Assists removal of trapped air and moisture.



Specifications & ordering information

Each die consists of five main parts: a base, body, plunger, and two internal pressing pellets. In addition to these there is a rubber O-ring for vacuum sealing and a plastic or metal ring for sample extraction. Tungsten internal pressing pellets are available for the 32 mm and 40 mm dies for XRF applications involving analysis of Fe.

Diameter	Maximum load	Complete Die	Base	Body	Plunger	Steel Pellets	Tungsten Pellets	O-ring	Extractor cap
5 mm	2 tonnes	GS03060	GS03050	GS03064	GS03063	GS03061	--	GS03062	GS03069
10 mm	5 tonnes	GS03100	GS03050	GS03104	GS03103	GS03101	--	GS03102	GS03025
13 mm	10 tonnes	GS03000	GS03050	GS03040	GS03030	GS03010	--	GS03020	GS03025
20 mm	25 tonnes	GS03165	GS03191	GS03169	GS03168	GS03166	--	GS03167	GS03521
32 mm	40 tonnes	GS26101	GS26141	GS26111	GS26121	GS26131	GS26133	GS26151	GS26161
40 mm	40 tonnes	GS26102	GS26141	GS26112	GS26122	GS26132	GS26134	GS26152	GS26161

United Kingdom
sales@specac.co.uk
+44 (0) 1689 892 902

United States
sales@specac.com
+1 866 726 1126

China
frank.li@specac.com

Singapore
kamhar.woo@specac.com

